


SMT-100

M.2 4-port Isolated RS-232/422/485 Serial Card



Features

- 4-port high-speed RS-232/422/485
- Each serial channel supports up to 2.5kV Isolation
- Up to 31.25Mbps super fast data transmission
- -40°C to 85°C Operating Temperature
- Flexible supports M.2 Key B, Key M
- Interrupt Status Register for Performance Enhancement





Specifications

Serial	
Interface	PCIe x1
Form-Factor	M.2 Key B-M
Chipset	EXAR XR17V354
Standard	RS-232/422/485 (2.5kV Isolation)
Number of Ports	4
Baud Rate	Up to 921.6kbps
FIFOs	256 byte
Flow Control	CTS/RTS, Xon/Xoff
Software Support	
OS	Windows 10/11, Linux

Mechanical	
Dimensions (W x L)	<ul style="list-style-type: none"> ▪ M.2 Card: 22mm x 80mm ▪ Cable Length : 250mm
Weight	145 g
Environment	
Operating Temperature	-40°C to 85°C (-40°F to 185°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% Humidity, non-condensing
Relative Humidity	95% @ 85°C
EMC	CE, FCC
Packing List	
1 SMT-100 Serial Card, 4 COM Cable, 2 Bracket	

Dimensions

Unit : mm/ inch



Order Information

SMT-100	Four Isolated Serial Port M.2 Card
---------	------------------------------------